nx filtration

Technical datasheet

WMC110 UF010

Hollow fiber ultrafiltration module for water and wastewater applications

Release TDS010 – WMC110 UF010, Rev. 01 - 20240704

nx filtration

Technical datasheet

WMC110 UF010

General Information

The WMC110 UF010 is a tight ultrafiltration module, used for potable water production, RO pretreatment, municipal and industrial wastewater treatment. These modules excel in removing colloidal silica, turbidity, suspended solids, and virus and bacteria while offering outstanding pH and chlorine resistance and excellent mechanical strength of the fibers. The WMC110 UF010 modules can be used as final polishing step – for example to remove colloidal silica from boiler feed water or in the soft drink industry.

Membrane characteristics

Membrane material	Modified PES
Membrane fiber inner diameter	0.7 mm (0.028”)
MWCO [1]	10 kDa
Filtration mode	Inside-Out; Vertical
Operation mode	Dead-end or cross-flow

Operating Conditions [2]

Typical flux	50 – 100 l/m²/h (30 – 60 gfd)
Backwash flux	100 – 250 l/m²/h (60 - 150 gfd)
Max. system pressure [3]	6 bar (87 psi)
Max. transmembrane pressure [3]	6 bar (87 psi)
Max. backwash pressure [3]	4 bar (58 psi)
Max. active chlorine concentration	500 ppm @ pH>10
Max. cumulative active chlorine exposure	250,000 ppm-hours @ pH>10
Max. particle size	150 µm
Max. TSS	300 ppm
Max. turbidity	150 NTU
Max. Temperature during operation & cleaning	40°C (104°F)
pH range during operation	2-12
pH range during cleaning	1-13

[1] Molecular Weight Cut Off (MWCO) is an estimation as it depends on size, shape, charge and polarity of the compound being tested, as well as test conditions. Testing was done with PEG.
[2] The limitations shown here are for general use. The values may be more conservative for specific projects to ensure the best performance and longest life.
[3] Maximum pressures at 20°C (68°F).

WMC110 UF010

Module Specification – Union

Materials of Construction

Housing	PVC-U
Potting	Epoxy resin

Dimensions

Membrane Surface Area	14.7 m²
L1.0	1546 mm (60.87”)
L1.1	132 mm (5.20”)
L2.0	1678 mm (66.08”)
L2.1	61 mm (2.40”)
D1.0	110 mm (4.33”)
D1.1	1.0” BSP
D1.2	5.0” BSP
D2.0	110 mm (4.33”)



Assembly Components

(1) Module	WMC110 UF
(2) Union end	TP 110mm Union End
(3) Nut	TP 110mm Wartel
(4) O-ring	TP End Cap O-ring 110mm

Available Sets (Components 1-4)	WMC110 UF010 Union Set	WMC110 UF010 Union US Set [5]
Set-Code	SETUF0023	SETUF0037

[5] US Sets include additional transition pieces (not shown) for permeate and feed/concentrate connections to allow for connection to standard US piping (permeate: 1”; feed/concentrate; 2.5”). For further information, please contact your local sales representative.

WMC110 UF010

Storage Information

New modules in original packaging can be stored for max. 1 year from shipping date in a dry place, protected from sunlight or any heat source, at temperatures between 1 and 40°C (33 and 104°F);

Ex-factory storage solution: 84wt% water, 15wt% glycerin and 1wt% sodium metabisulfite;

Weight Information

Weight	WMC110 UF010 Union Set
Dry weight Module including assembly components	12.5 kg (28 lbs)
Filled Module including assembly components	25 kg (55 lbs)

Shipping Information

Each module is individually packed in a vacuum sealed plastic bag. Modules and assembly components are shipped in the same cardboard box:

- Shipping weight per box: 15 kg (33 lbs.);
- Box dimensions: 180 x 25 x 25 cm; 70.9 x 9.8 x 9.8 in (L x W x H);

Haaksbergerstraat 95
7554 PA Hengelo
The Netherlands

+31 (0)850 479 900
info@nxfiltration.com
www.nxfiltration.com

The statements, technical information and recommendations contained herein are believed to be accurate at the date of publication. Since the conditions and methods of use of the product and/or the information referred to herein are beyond our control, NX Filtration B.V. expressly disclaims any and all liability as to any results obtained from or arising out of any use of the product and/or reliance on such information. NO WARRANTIES OR GUARANTEES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OF TITLE, OF NONINFRINGEMENT OF THIRD-PARTY RIGHTS OR ANY OTHER WARRANTY ARE MADE CONCERNING THE PRODUCTS DESCRIBED AND/OR THE INFORMATION PROVIDED HEREIN.

©2024 NX Filtration B.V. | All rights reserved worldwide